

SolarSpring Outdoor-Set

is a compact and innovative water treatment plant. It guarantees a reliable and safe water supply from dirty and microbiological contaminated water sources without using chemicals. Automatic operation, low maintenance and easy plug & play setup are the features of this system.



Specification – SolarSpring Outdoor-Set	
Application	Water purification from turbid and microbiological contaminated water
Raw water source	Rivers, lakes, wells, boreholes and contaminated tap water
Water quality	Up to 99.999 % retention of microorganisms, bacteria and viruses
Nominal flow capacity	100 l/h (100 - 200 l/h possible)
Supply capacity	Up to 2,4 (max. 4,8) m ³ /day
Filtration yield	99%
Power consumption	40 W
Dimensions	1200 x 400 x 168 mm (LxWxH)
Weight	22 kg
Housing	PP Transport-Box
IP degree of protection	IP65
Pre-treatment	Screen filter 1,000 µm
Main-treatment	High quality UF-module with robust multi-bore membrane 2.5 m ² / 0.02µm and automatic back flush system
Post-treatment	Optional
Operation	Automatic PLC controlled operation with display and data logger
Power source	Solar (12 VDC) or grid (100-240 VAC 50/60Hz)
Ambient temperature	0-50°C
Water temperature	2-40°C
Feed turbidity	Standard membrane <50 NTU / max. 100 NTU (short term peaks) Heavy membrane <200 NTU / max. 400 NTU (short term peaks)
Filtration pressure	0.1 – 1.5 bar
System pressure	1.0 – 2.5 bar
Backwash pressure	3.0 bar
Energy demand	0.3 kWh/m ³
Feed pump flow range	50 -200 l/h (PWM controlled)
Max. feed pump pressure	3.5 bar
Max. system pressure	6 bar
Set including	<ul style="list-style-type: none"> • mobile water purification system • integrated surface feed pump • Solar package including: <ul style="list-style-type: none"> Outdoor solar panel 100Wp, 12V Solar charge controller 10A, 12V High cycle AGM battery 12Ah, 12 V
Optional accessories	<ul style="list-style-type: none"> • Submersible feed pump 12 V (up to 40m) • Service cleaning package (CIP)